

# PS500

## Compact, Light Weight Floor Scale



*Shown with optional floor stand*

- **Accuracy**– 0.2% of full capacity
- **Capacity**– 500 lb (250 kg)
- **Construction**– Low profile stainless steel platform with mild steel understructure and stainless steel/ABS indicator.
- **Platform Size**– 22" x 22", 22" x 36", and 22" x 42"
- **Protocol**– Standard NCI interfaces to most common shipping software, including UPS™ Worldship Online and FedEx®. Not legal for trade
- **Display**– Five 0.625" digits LCD
- **Power**– Battery or AC power
- **Operator Keys**– On/Off/Zero, Tare, Units (lb/kg), Hold/Print
- **Options**– Floor and table top stands for the weight indicator

# PS500 Compact, Light Weight Floor Scale

## Features

Salter Brecknell PS500 offers a convenient, compact and portable weighing capability with high capacity.

This durable product offers unparalleled weighing performance, with the advantages of low profile and affordability.

Standard features include lbs, kg and lb/oz weighing modes, weight hold feature, stable weight indication and auto power off to extend battery life.

Operates on four (4) AAA batteries or AC adapter (both included). Also included is a rubber slip reducing mat, an indicator bracket for stand or wall mounting, and a RS-232 cable.

PS500 comes with a stainless steel top, allowing for easy wipedown.

Not legal for trade.



*Shown with optional floor stand*



*Shown with optional table top stand*

## Specifications

**Capacity**– 500 lb x 0.2 lb (250 kg x 0.1 kg)

### Platform Size–

Scale: 22" L x 22" W x 2" H

559 mm (L) x 559 mm (W) x 51 mm (H)

36" L x 22" W x 2" H

914 mm (L) x 559 mm (W) x 51 mm (H)

42" L x 22" W x 2" H

1067 mm (L) x 559 mm (W) x 51 mm (H)

**Indicator**– 6.5" L x 3.2" H x 1.2" W

164 mm (L) x 81 mm (H) x 29 mm (W)

**Display**– Five 0.625" digits LCD

**RS-232**–10' interface cable (DB-9) (included) **Keyboard**–

Hold/Print, Units, Tare, On/Off/Zero

**Units**– lb, kg, lb/oz

**Power**– Four (4) AAA batteries or 6 VDC, 500mA adapter (both included)

**Battery Life**– 20 hours

**Operating Temp**– 41° F to 95° F (5° C to 35° C)

### Packaging Dimensions–

Scale: 26" L x 24" W x 4" H

660 mm (L) x 609 mm (W) x 101 mm (H)

39" L x 24" W x 4" H

965 mm (L) x 609 mm (W) x 101 mm (H)

44" L x 24" W x 4" H

1117 mm (L) x 609 mm (W) x 101 mm (H)

### Shipping Weight–

35 pounds (16 kg) - 22" (607 mm)

57 pounds (26 kg) - 36" (914 mm)

63 pounds (29 kg) - 42" (1067 mm)

### Options–

Table top stand (not included)

Stand height: 19.125" (486 mm); weight 3 lb (1.5 kg)

Stand base: 6" W x 3" L x 1" H

152 mm (W) x 76 mm (L) x 25 mm (H)

Floor stand (not included)

Stand height: 36" (914 mm); weight 11 lb (5 kg)

Stand base: 11.5" L x 11.5" W x 0.75" H

292 mm (L) x 292 mm (W) x 19 mm (H)

**Certifications**– Full FCC compliance, UL/CUL power adapter