

RD-65

Remote Display CE



- **Highly Durable**– Powder coated mild steel enclosure (IP65) with wall mount swivel bracket or easy to install hanging rings. Adjustable sun visor included.
- **Serial Port**– RS-232, RS-485 or current loop with selection up to 16 protocols, three data formats and eight types of baud rates
- **Display**– Double row ultra bright large 127 mm / 5", six Digit LED Display visible up to 46 m / 150'
- **Displays up to 999,999 or down to -99,999**
- **Annunciator**– kg, lb, G (gross), N (net)

RD-65 Remote Display

Specifications

Enclosure:

Powder Coated, Mild Steel
Non Glare Lens

Operating Temperature:

-15° C to 50° C / -5° F to 122° F

Display:

Display Type: 127 mm / 5" seven segment red LED display
Annunciators: kg, lb, G (gross), N (net)
Display Characters: 999,999 to -99,999

Communication Interface:

Serial Cable Length 10 m / 32'
Serial Port: RS-232, RS-485 or Current Loop
Data Format: 8N1, 7E1 or 7O1
Baud Rate: 110, 300, 600, 1200, 2400, 4800, 9600 or 19200

Compatible with Most:

Brecknell, Dillon, Avery Weigh-Tronix, GSE, Cardinal, Rice Lake & Transcell indicators

Power:

Input: 120VAC , 60Hz
Transformer Output: 24VAC, 2 amp (UL, Waterproof)
Current Draw: <1500mA
Fused: 2.0 amp

Optional Power Supply:

Input: 220VAC , 50Hz
Transformer Output: 20VAC, 2 Amp (Waterproof)
Current Draw: <700mA
Fused: 2.0 amp
AWT05-505706: UK PSU

Shipping Specifications:

Weight: 20 kg / 45 lb

Package Dimensions:

464 mm x 448 mm x 999 mm / 39.3" x 18.3" x 17.6"

Certification: CE

Warranty:

One Year from Shipment

Product Code:

816965004638 - US
816965004744 - RoW



Dimensions

