

# SBI-505



## Indicator



- **Display Resolution**– Up to 30,000
- **Internal ADC**– 2,000,000
- **Load Cell Capability**– 6 @ 350 ohm
- **Construction**– Painted mild steel with stainless steel desk stand
- **Finish**– Powder coat paint
- **Time and Date**– Standard
- **RS-232**– Standard DB9 connection
- **Rated**– IP65
- **Function**– Checkweighing, count, weight, total and print
- **Power**– AC adapter (included) or external customer supplied 12Vdc

VALUE IN  
WEIGHING

# SBI-505 Indicator

---

## Specifications

---

**Construction:** Painted mild steel with stainless steel desk stand or wall mount stand

**Dimension:** 47 mm (W) x 220 mm (L) x 149 mm (H)  
1.875" W x 8.675" L x 5.875" H

**Finish:** Powder coat paint

**Rated:** IP65

**Load Cell Capability:** 6 @ 350 ohm

**Excitation:** 5 VDC

**Internal ADC:** 2,000,000

**Display Resolution:** up to 30,000

**Display:** Six digit 20 mm / 0.8" high red LED

**Annunciators:** -0-, motion, Gross, Net, tared, Total, pcs, lb, kg, Lo, OK, Hi

**Interface Cable Connectors Included**

**Optional 15' Interface Cable:** AWT05-505848

**Optional Power Supply:**

**AWT05-505962:** EU PSU

**AWT05-505961:** UK PSU

**RS-232:** Female DB9 connection

**Time and Date:** Military format

**Operator Keys:** On/Off, Total, Count, kg/lb, Gross, Tare, Zero, Print

**Operating Temperature:**

-10° C to 40° C / 14° F to 104° F

**Power:** 120/220VAC 60Hz/50Hz

**Output:** 9 VDC - 12 VDC center positive

**Calibration:** Front panel accessible

**Accuracy:** NTEP at 5,000 divisions, Class III

**Shipping Weight:** 1.7 kg / 3.75 lb

**Packaging Dimensions:**

279.5 mm (L) x 184 mm (W) x 266.5 mm (H)

11" L x 7.25 W x 10.5 H

**Certifications:** NTEP CC #11-082, AM-5885

**Product Code:** AWT05-505729

**Packaging Contents:** Indicator, stand, power supply, manual, RS-232 connector, lead seal, load cell connector and knobs

## Options

---

